FENELLA™ BSD 295-C

Metal Working Neat SS Bolt & Screw forming oil

DESCRIPTION

FENELLA BSD 295-C is a special oil for cold heading and drawing operations.

FENELLA BSD 295-C is a special metal working oil for cold heading and drawing operations of stainless steel. The high content of chlorine-free EP-additives guarantees a long tool life. The additives allows the use of the oil as dual purpose oil also for machine lubrication.

FENELLA BSD 295-C is based on specially refined mineral oil and contains a combination of chemically active and polar additives. The additives are selected to provide the oil with high load carrying properties.

FENELLA BSD 295-C discolours yellow metals. Optimum viscosity for heat dissipation. Good die life

FEATURES

- Excellent for Cold heading of Stainless steel
- High EP and Boundary lubrication
- Do not use for Non-Ferrous metals
- Excellent for machine lubrication
- Good Die life

TYPICAL VALUES

Product Appearance	Brown Oil
Copper Corrosion (ASTM D 130):	4C
Specific Gravity @29.5°C (ASTM D 4052):	0.902 kg/L
Kinematic Viscosity @40°C (ASTM D 455):	67 cSt
Flash Point (ASTM D 92):	150°C

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D001D4326



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com

FENELLA™ BSD 295-C

Metal Working Neat SS Bolt & Screw forming oil

REFERENCES

Houghton recommends that periodic checks of FENELLA BSD 295-C should be carried out.

Checks will involve:

Viscosity@40°C: 56.9-77 cSt (In-use) Water Content: < 0.02% (In-use)

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

HOW TO USE

FENELLA BSD 295-C is used neat, as supplied, from the drum.

Apply by: Spraying, brushing or flooding.

FENELLA BSD 295-C can be diluted with light oil for light machining operations.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for FENELLA BSD 295-C is a minimum of Twelve (12) months, unless otherwise specified. The product should be stored inside (5-40°C) for no more than 1 year and be protected from freezing.

FENELLA BSD 295-C is available in Pail, Drum or Tote. Other sizes may be available upon request , please contact your Houghton sales representative.

01 July 2011 Version 1.0, Code: D001D4326

RELATED PRODUCTS

- CUT-MAX[®]: Straight cutting oils
- GARIA™: Straight cutting oils
- MACRON™: Straight cutting and honing oils
- EXCELENE™: Straight cutting and honing oils
- DASCOLENE™: Straight OEM approved cutting oils
- HOCUT®: Water miscible metalworking fluids
- DASCOOL™: Water miscible metalworking fluids
- DROMUS™: Soluble metalworking fluids
- ADRANA™: Micro-emulsion metalworking fluids
- SITALA[™]: Semi-Synthetic metalworking fluids
- METALINA™: Synthetic metalworking fluids
- HOUGHTO-GRIND®: Straight and water miscible grinding fluids
- HOUGHTO-DRAW®: Straight and water miscible drawing stamping and forming fluids.
- CINDOL™: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- FENELLA™: Straight and water miscible drawing, stamping and forming fluids.
- CERFA-KLEEN®: Water miscible cleaning fluids
- VIBRA-KLEEN®: Water miscible vibrating cleaning fluids
- CALLINA™: Water miscible cleaning fluids
- RUST VETO®: Straight and water miscible rust preventive fluids.
- ENSIS™: Straight and water miscible rust preventive fluids.
- COSMOLINE®: MIL-SPEC Straight and water miscible rust preventive fluids.



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com