HOUGHTO-GRIND® 260

Low Viscosity Grinding Oil

DESCRIPTION

HOUGHTO-GRIND 260 is a colorless and odorless grinding oil designed for use in grinding machines with ultra fine filtration systems. The low viscosity of HOUGHTO-GRIND 260 results in rapid heat removal, longer grinding wheel life, greater flow rates through the filtration system, lower dragout and less residue on machine surfaces and components.

HOUGHTO-GRIND 260 is formulated using a pure hydrotreated single cut base oil that results in lower misting and greatly reduced smoke generation when compared to conventional grinding oils. High production to dressing ratios can be expected as a norm while using HOUGHTO-GRIND 260.

HOUGHTO-GRIND 260 can be filtered to below one micron without altering product chemistry or efficacy.

FEATURES

- Odourless
- Rapid heat removal
- Longer Grinding wheel life
- Reduce residue on machine and components
- Reduce smoke generation.
- Long lasting due to easy filterability.
- Can be use also on non-ferrous Alloys

TYPICAL VALUES

Product Appearance	Water White Oil
Flash Point (COC)	> 121°C
Specific Gravity @15 °C	0.830 kg/L
Viscosity @40 °C	4.0 cSt
Aromatics %	< 0.5
Boiling Point	271°C

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: HTG 260



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

HOUGHTO-GRIND® 260

Low Viscosity Grinding Oil

REFERENCES

Houghton recommends that periodic solution checks of HOUGHTO-GRIND 260 should be carried out .

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

HOW TO USE

HOUGHTO-GRIND 260 is used neat, as supplied, from the drum.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for HOUGHTO-GRIND 260 is a minimum of Twelve (12) months, unless otherwise specified.

HOUGHTO-GRIND 260 is available in Pail, Drum or Tote. Other sizes may be available upon request, please contact your Houghton sales representative.

RELATED PRODUCTS

- CUT-MAX: Straight cutting oils
- GARIA: Straight cutting oils
- MACRON: Straight cutting and honing oils
- DASCOLENE: Straight OEM Approved cutting oils
- WIOLAN: Straight honing and grinding oils
- HOCUT: Water miscible metalworking fluids
- DROMUS: Soluble metalworking fluids
- SUPERCUT PLUS: Economical Soluble metalworking fluids
- ADRANA: Water miscible metalworking fluids
- SITALA: Semi-Synthetic metalworking fluids
- METALINA: Synthetic metalworking fluids
- HOUGHTO-GRIND: Straight and water miscible grinding fluids
- HOUGHTO-DRAW: Straight and water miscible drawing stamping and forming fluids.
- CINDOL: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- CERFA-KLEEN: Water miscible cleaning fluids
- CALLINA: Water miscible cleaning fluids
- RUST VETO: Straight and water miscible rust preventive fluids.
- ENSIS: Straight and water miscible rust preventive fluids.

01 July 2011 Version 1.0, Code: HTG 260



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.