MACRON[™] 2429 S-8

Neat Metal Grinding Oil for Carbide Tools

DESCRIPTION

MACRON 2429 S-8 is a high performance grinding oil, used for grinding of high speed steel and cemented carbide, with ceramic, diamond and boron nitrite (CBN) grinding wheels.

MACRON 2429 S-8 can also be used for machining of light alloyed steels, yellow metals and light metals (Mg) and glass at high cutting speeds.

MACRON 2429 S-8 is based on hydrotreated mineral oils with a very low aromatic content. A combination of polar, extreme pressure and anti wear additives provide the oils with high load carrying properties.

MACRON 2429 S-8 provides good tool live and good surface finish of the machined workpieces. High efficient anti mist additives reduce the mist load in the air.

MACRON 2429 S-8 has no risk of staining yellow metals.

FEATURES

- Excellent for Grinding and honing
- Excellent tool and die life
- Low Foam
- Excellent surface finish
- High flash point
- No staining on Yellow metals

TYPICAL VALUES

Product Appearance	Light Yellow Oil
Flash Point (COC)	> 165°C
Specific Gravity @29.5°C (ASTM D 4052)	0.815 kg/L
Viscosity @40°C	7.5 cSt
Copper Corrosion	1b

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 July 2011 Version 1.0, Code: D901L3245



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com

MACRON[™] 2429 S-8

Neat Metal Grinding Oil for Carbide Tools

REFERENCES

Houghton recommends that periodic checks of MACRON 2429 S-8 should be carried out.

Checks will involve:

Viscosity@40°C: 6.5 - 9.8 cSt (In-use) Water Content: < 0.02% (In-use)

These can be routinely performed and organised through Houghton's Customer Service laboratory, please contact your sales representative for further information about this service.

HOW TO USE

MACRON 2429 S-8 is used neat, as supplied, from the drum.

Apply by: Spraying, brushing or flooding.

The product MACRON 2429 S-8 can also be used for universal machining of light alloyed steels, yellow metals and light metals.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for MACRON 2429 S-8 is a minimum of Twelve (12) months, unless otherwise specified.

MACRON 2429 S-8 is available in Pail, Drum or Tote. Other sizes may be available upon request , please contact your Houghton sales representative.

RELATED PRODUCTS

- CUT-MAX[®]: Straight cutting oils
- GARIA™: Straight cutting oils
- MACRON™: Straight cutting and honing oils
- EXCELENE™: Straight cutting and honing oils
- DASCOLENE™: Straight OEM approved cutting oils
- HOCUT®: Water miscible metalworking fluids
- DASCOOL™: Water miscible metalworking fluids
- DROMUS™: Soluble metalworking fluids
- ADRANA™: Micro-emulsion metalworking fluids
- SITALA[™]: Semi-Synthetic metalworking fluids
- METALINA™: Synthetic metalworking fluids
- HOUGHTO-GRIND®: Straight and water miscible grinding fluids
- HOUGHTO-DRAW[®]: Straight and water miscible drawing stamping and forming fluids.
- CINDOL™: Straight and water miscible drawing and forming fluids especially for Aluminium parts.
- FENELLA™: Straight and water miscible drawing, stamping and forming fluids.
- CERFA-KLEEN®: Water miscible cleaning fluids
- VIBRA-KLEEN®: Water miscible vibrating cleaning fluids
- CALLINA™: Water miscible cleaning fluids
- RUST VETO®: Straight and water miscible rust preventive fluids.
- ENSIS™: Straight and water miscible rust preventive fluids.
- COSMOLINE®: MIL-SPEC Straight and water miscible rust preventive fluids.

01 July 2011 Version 1.0, Code: D901L3245



D.A. Stuart India Private Limited Plot No. 32A. HUDA Enclave, Jubilee Hills, Hyderabad Andhra Pradesh 500033 India Phone: +91 (40) 2354-1250 Fax: +91 (40) 2354-4869 info@houghtonindia.com www.houghtonindia.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.